

Application

The HJ-445 inverted louver blade equipment screen provides an effective and attractive sight screen around equipment and is designed for both interior and exterior installations. The HJ-445 is available in a wide array of finishes including custom color matching.

Standard Construction



- Material:** Mill finish 6063-T5 extruded aluminum.
- Frame:** 2" x 2" x 1/4" thick (51 x 38 x 25) angle.
- Blades:** 45° x 0.081" (2) thick J-style.
- Mullion:** Visible.
- Minimum Size:** 12" x 12" (305 x 305).
- Maximum Size:** Single section: 72" x 144" (1829 x 3658).
144" x 72" (3658 x 1829).
Multiple section: Unlimited

Options

- Factory finish:
 - High Performance Fluoropolymer - 100% resin Newlar®/70% resin Kynar®
 - Baked Enamel
 - Clear or Color Anodized, Class 1
 - Prime Coat
- Heavy duty 0.125" (3) construction.
- Welded construction.
- Hinged frame.

Ratings


Free Area: [48" x 48" (1222 x 1222) unit]: 8.1 ft² (0.75 m²)
50.6%




Model HJ-445
(standard)

*Dimensions furnished
approximately 1/2" (13) undersize.

Vertical Section



Vertical Mullion
(standard)



Horizontal Mullion
(standard)

Extruded Aluminum Louvers **HJ445** (1/2) June 2014